

Поршневые полугерметичные компрессоры DORIN

Серия	Модель	Об. производительность	Кол- во цил.	Область применения		Цена, евро с НДС	Запр. маслом (кг)	Соединение		Вес, нетто, кг
		(куб.м/час)		R404A/R50 7 R407C*	R134A			Всасывани е	Нагнетани е	
H1	H51CS	3,86	2	M	H	907	1,0	12s	12s	35
	H80CC	3,86	2	H	H	916	1,0	12s	12s	36
	H80CS	5,3	2	M	H	916	1,0	16s	12s	36
	H101CC	5,3	2	H	H	921	1,0	16s	12s	37
	H101CS	6,75	2	M	H	921	1,0	16s	12s	37
	H151CC	6,75	2	H	H	931	1,0	16s	12s	38
	H151CS	7,71	2	M	H	931	1,0	16s	12s	38
	H181CC	7,71	2	H	H	944	1,0	16s	12s	39
	H181CS	8,47	2	M	H	944	1,0	16s	12s	39
	H201CC	8,47	2	H	H	990	1,0	16s	12s	40
	H201CS	9,88	2	M	H	936	1,0	18s	16s	40
	H221CC	9,88	2	H	H	1022	1,0	18s	16s	41
	H221CS	10,85	2	M	H	1022	1,0	18s	16s	41
	H251CC	10,85	2	H	H	1022	1,0	18s	16s	41
	H251CS	12,17	2	M	H	1066	1,0	18s	16s	41
	H281CC	12,17	2	H	H	1066	1,0	18s	16s	43
	H281CS	13,23	2	M	H	1108	1,0	18s	16s	44
H2	H290CS	14,74	2	M	H	1201	1,4	22s	16s	54
	H300CC	14,74	2	H	H	1233	1,4	22s	16s	54
	H300CS	15,94	2	M	H	1233	1,4	28s	16s	54
	H350CC	15,94	2	H	H	1233	1,4	28s	16s	54
	H350SB	17,53	2	L	H	1233	1,4	28s	16s	54
	H380CC	17,53	2	H	H	1436	1,4	28s	16s	56
	H380SB	19,53	2	L	H	1269	1,4	28s	16s	56
	H390CS	19,53	2	M	H	1436	1,4	28s	16s	56
	H392CS	23,31	2	L	H	1491	1,4	28s	16s	56
H3 2	H403CC	19,98	2	H	H	1668	2,0	28s	16s	75
	H403CS	22,83	2	M	H	1668	2,0	28s	16s	76
	H503CC	22,83	2	H	H	1694	2,0	28s	16s	79
	H503CS	26,44	2	M	H	1772	2,0	35s	16s	80
	H743CC	26,44	2	H	H	1879	2,0	35s	16s	81
H3 5	H401CS	19,29	4	M	H	1798	2,0	22s	18s	89
	H451CC	19,29	4	H	H	1830	2,0	22s	18s	91
	H451CS	23,13	4	M	H	1870	2,0	28s	18s	89
	H551CC	23,13	4	H	H	1898	2,0	28s	18s	91
	H551CS	27,33	4	M	H	1926	2,0	28s	22s	91
	H701CC	27,33	4	H	H	1969	2,0	28s	22s	91
	H701CS	31,88	4	M	H	1969	2,0	28s	22s	91
	H751CC	31,88	4	H	H	2012	2,0	28s	22s	91
	H751CS	38,06	4	M	H	2012	2,0	35s	22s	91
	H1002CC	38,06	4	H	H	2038	2,0	35s	22s	101
	H801CS	43,73	4	M	H	2067	2,0	35s	22s	91
	H1003CC	43,73	4	H	H	2094	2,0	35s	22s	101
	H851CS	42,81	4	M	H	2323	2,5	35s	28s	125
	H1201CC	42,81	4	H	H	2446	2,5	35s	28s	130

Серия	Модель	Об. производительность	Кол- во цил.	Область применения		Цена, евро с НДС	Запр. маслом (кг)	Соединение		Вес, нетто, кг
		(куб.м/час)		R404A/R50 7 R407C*	R134A			Всасывани е	Нагнетани е	
H4 1	H1001CS	48,82	4	M	H	2491	2,5	35s	28s	127
	H1501CC	48,82	4	H	H	2581	2,5	42s	28s	131
	H1501CS	56,87	4	M	H	2884	2,5	35s	28s	127
	H2001CC	56,87	4	H	H	3021	2,5	42s	28s	131
	H1601CS	63,76	4	M	H	3263	2,5	42s	28s	134
	H2201CC	63,76	4	H	H	3338	2,5	42s	28s	136
H5	H2000CS	75,83	4	M	H	4047	3,5	42s	28s	190
	H2500CC	75,83	4	H	H	4111	3,5	54s	28s	185
	H2500CS	85,01	4	M	H	4188	3,5	54s	28s	185
	H3000CC	85,01	4	H	H	4332	3,5	54s	28s	199
	H2700CS	92,25	4	M	H	4313	3,5	54s	35s	200
	H3200CC	92,25	4	H	H	4514	3,5	54s	35s	205
	H2900CS	102,35	4	M	H	4438	3,5	54s	35s	205
H6	H3400CC	102,35	4	H	H	4615	3,5	54s	35s	205
	H3000CS	113,74	6	M	H	5373	3,5	54s	35s	236
	H3500CC	113,74	6	H	H	5547	3,5	54s	35s	246
	H3500CS	127,52	6	M	H	5547	3,5	54s	35s	233
	H4000CC	127,52	6	H	H	5825	3,5	54s	35s	249
	H4000CS	138,37	6	M	H	6140	3,5	54s	42s	244
	H4500CC	138,37	6	H	H	6354	3,5	54s	42s	252
	H4500CS	153,52	6	M	H	6354	3,5	54s	42s	253
H7	H5000CC	153,52	6	H	H	6507	3,5	54s	42s	253
	H5000CS	164,3	8	M	H	7968	8,5	66s	42s	350
	H5500CC	164,3	8	H	H	8120	8,5	66s	42s	355
	H5500CS	184,19	8	M	H	8120	8,5	80s	42s	350
	H6000CC	184,19	8	H	H	8448	8,5	80s	42s	355
	H6000CS	199,86	8	M	H	8448	8,5	80s	42s	355
	H7500CC	199,86	8	H	H	8952	8,5	80s	42s	357
	H7501CS	221,75	8	M	H	8952	8,5	80s	54s	355
	H8001CC	221,75	8	H	H	9432	8,5	80s	54s	357
	H8000CS	244,78	8	M	H	9872	8,5	80s	54s	360
	H9000CC	244,78	8	H	H	9872	8,5	80s	54s	366

H Высокотемпературный режим кипения +5C/+10C

M Среднетемпературный режим кипения -5C

L Низкотемпературный режим кипения -20C

* - только модели CC

Модель	Об. производительность	Кол- во цил.	Область применения		Цена , евро с НДС	Запр. масло м (кг)	Соединение		Вес, нетто , кг
	(куб.м/час 20/50/90 Hz)		R404A/R507 R407C	R134 A			Всасывани е	Нагнетани е	
HI 100 CC INVERTER (POE32)	2.12 5.30 9.54	2	M-H-L	M-H	1150	1,0	18s	12s	43
HI 150 CC INVERTER (POE32)	2.70 6.75 12.15	2	M-H-L	M-H	1162	1,0	18s	16s	44
HI 240 CC INVERTER (POE32)	3.81 9.52 17.14	2	M-H-L	M-H	1275	1,0	22s	16s	50
HI 361 CC INVERTER (POE32)	5.40 13.50 24.30	4	M-H-L	M-H	2125	2,0	28s	22s	93
HI 421 CC INVERTER (POE32)	6.48 16.19 29.14	4	M-H-L	M-H	2192	2,0	28s	22s	93
HI 451 CC INVERTER (POE32)	7.72 19.29 34.72	4	M-H-L	M-H	2241	2,0	28s	22s	93
HI 551 CC INVERTER (POE32)	9.25 23.13 41.63	4	M-H-L	M-H	2254	2,0	35s	22s	93
HI 701 CC INVERTER (POE32)	10.93 27.33 49.19	4	M-H-L	M-H	2339	2,0	35s	28s	93
HI 751 CC INVERTER (POE32)	12.75 31.88 57.38	4	M-H-L	M-H	2388	2,0	35s	28s	93
HI 1201 CC INVERTER (POE32)	17.12 42.81 64.22	4	M-H-L	M-H	2689	2,5	42s	25s	132
HI 1501 CC INVERTER (POE32)	19.53 48.82 73.23	4	M-H-L	M-H	2839	2,5	54s	35s	140

H Высокотемпературный режим кипения +5C/+10C

M Среднетемпературный режим кипения -5C

L Низкотемпературный режим кипения -20C